Mites
The Work We Know

MPP 1000 EX PALLET FUEL PUMP

It works with the logic that the pallets on the rotor aligned with the pump shaft absorb the fuel from the outside and transfer it to the outlet with a high flow rate. Pallet selection can be made depending on the type of fuel to be used. It provides long-lasting use thanks to pallets made of composite material. Since the pallets will break in a negative situation that may occur inside the pump due to stress, dirt, etc., it has a longer life than other pump types thanks to easy and affordable replacement. It is specially produced for fuel oil. Mechanical seal is used for sealing on the shaft.

Product Type:	Gasoline-Carosene-Diesel
Flow (QMin-QMax):	100-1000 L/min
Ambient Operating Temperature:	-25°C / +55°C
Transfer:	640 Dv/min
Weight:	68 Kg
Dimension (LxWxD):	490×420×420mm
Flange Diameter:	3"
Pump Body:	Cast Iron (PIG GG25)

- PALETLİ POMPA TEKNİK ÖZELLİK TABLOSU -

ÜRÜN KODU	MTS-MPP300	MTS-MPP500	MTS-MPP1000	MTS-MPP1500
ÇAP	50mm / 2"	65mm / 2½"	80mm / 3"	100mm / 4"
DEVİR	400-640 rpm	400-640 rpm	400-640 rpm	500 rpm
KAPASİTE	150-300 L/dk	300-500 L/dk	600-1000 L/dk	1500-1900 L/dk
VAKUM	0.5 bar			
ÇALIŞMA BASINCI	5 bar			
ÇALIŞMA SICAKLIĞI	-20 / +60 °C			
MOTOR GÜCÜ	2.2kW	4kW	7.5kW	18.5kW
ÖLÇÜLER (mm)	400x350x350	460x340x370	490x420x420	580x550x610
NET AĞIRLIK (kg)	33	40	68	160
BRÜT AĞIRLIK (kg)	34	47	74	178

Product No: TDR2000001413